

CAMERA TYPE	WIRED FLUSH-MOUNT (also known as rear)	CAMERA TYPE	WIRED WRAP-MOUNT (also known as side)
Wired	Connects to a router with an M12/RJ45 network cable	Wired	Connects to a router with an M12/RJ45 network cable
Micro-SD	Built-in 64 GB micro-SD card	Micro-SD	Built-in 64 GB micro-SD card
Lens	3.3 mm with day and night functionality	Lens	3.3 mm with day and night functionality
Supported resolution	Up to 1080p, 30 frames per second	Supported resolution	Up to 1080p, 30 frames per second
Streaming and recording	720p, 30 frames per second	Streaming and recording	720p, 30 frames per second
Field of view	Horizontal: 106°; vertical: 55.8°; diagonal: 126° Manual angle adjustment	Field of view	Horizontal: 106°; vertical: 55.8°; diagonal: 126° Manual angle adjustment
Night view distance	30 ft (9.14 m)	Night view distance	30 ft (9.14 m)
Waterproof and dustproof	IP69K	Waterproof and dustproof	IP69K
Power	12 or 24V DC	Power	12 or 24V DC
Power consumption	200 mA at 12V	Power consumption	200 mA at 12V
Reset button	Included	Reset button	Included
Operating environment	Temperature with infrared on: -4° to 104° F (-20° to 40° C)  Temperature with infrared off: -4° to 140° F (-20° to 60° C)  Humidity: 20% to 55%, non-condensing	Operating environment	Temperature with infrared on: -4° to 104° F (-20° to 40° C)  Temperature with infrared off: -4° to 140° F (-20° to 60° C)  Humidity: 20% to 55%, non-condensing
Dimensions	3.5 x 1.5 x 3.5 in (8.9 x 3.9 x 8.9 cm)	Dimensions	3.5 x 1.5 x 3.5 in (8.9 x 3.9 x 8.9 cm)
Weight	.99 lb (449 grams)	Weight	.61 lb (276.7 grams)
SKU	SRF-AUX-S51-03P	SKU	SRF-AUX-S51-04P
Accessories	1 mounting bracket	Accessories	2 small hose clamps, 2 large hose clamps



**IMPORTANT:** The purpose of this **DRAFT** document is to educate the Lytx and Reseller-Partner sales and marketing teams on selling, marketing, messaging, and positioning points for the Surfsight® auxiliary cameras. Please note that this document has not yet been regionalized and **is subject to change**. This document is for **Reseller-Partner use only**.

NOTE: The power cable comes attached to the camera. M12/RJ45 network extension cables (five or twenty meters) can be purchased through the order form.

